Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-181-3008

## **Body Style:**

Right angle type

## **Overall Length:**

Between 5.675 inches and 5.705 inches

#### **Overall Height:**

0.670 inches

#### **Overall Width:**

0.370 inches

#### **Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

## **Unthreaded Mounting Hole Diameter:**

#### 0.070 inches

Distance Between Mounting Facility Centers:

Between 5.320 inches and 5.340 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

#### **Polarization Method:**

Contact

#### **End Application:**

5815-01-062-8194

#### **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic polyester single mating end

## Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class

2 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single materia

# Insert Material Specification:

Ail-m-24519, ty ant-30f military specification single material response single mating end



Included Contact Quantity:

100 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.100 gold grains, troy

# **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.