Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-181-3522

# **Thread Class:** 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Height:** 0.937 inches **Overall Width:** 0.937 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.719 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell Mating End Quantity: 1 **Contact Position Arrangement Style:** 5 number 20 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 35.0 and 140.0 and 205.0 and 275.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Length:** 0.290 inches

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):

#### 24

Thread Size:

0.625 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic epoxy single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Shell Material Specification:

Qq-a-367 federal specification single material response

## Included Contact Quantity:

5 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.005 gold grains, troy

**Precious Material:** 

Gold

## Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

## **Specification Data:**

81349-mil-c-83723/72 government specification

Shelf Life:

N/a

# Unit Of Measure:

Electrical Receptacle Connector - Page 3 of 3



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.