

View Online at <https://aerobasegroup.com/nsn/5935-01-181-4747>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.500 inches

Overall Diameter:

0.650 inches

Environmental Protection:

Salt water resistant and vibration resistant and shock resistant and humidity resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Frequency Rating:

500.0 megahertz single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

78.0 single mating end all contact groupings

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end all contact groupings

Included Contact Quantity:

1 single mating end 2nd contact grouping

Special Features:

Coaxial series twin, type twtnc

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.