NSN 5935-01-181-6598

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-181-6598

Overall Length: 1.350 inches **Overall Height:** 0.812 inches **Environmental Protection:** Moisture resistant and salt water resistant and thermal shock resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping or silver single mating end single contact grouping or tin single mating end single contact grouping **Insert Material:** Plastic polypropylene single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Zinc **Shell Surface Treatment:** Nickel **Included Contact Quantity:**

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

NSN 5935-01-181-6598

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location

Contact surface gold or contact surface silver

Precious Material And Weight:

0.005 gold grains, troy or 0.005 silver grains, troy

Precious Material:

Gold or silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0