NSN 5935-01-181-6607

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-181-6607

Body Style:Straight shape

Overall Length:

1.541 inches

Overall Height:

Between 3.095 inches and 3.125 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.790 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.427 inches and 1.447 inches

Distance From Mounting Shoulder To Front Face:

Between 0.764 inches and 0.768 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

57 all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp all mating ends single contact grouping

Guide Design And Location:

Hexagon shape male post right-hand at 12 oclock

NSN 5935-01-181-6607

Electrical Receptacle Connector - Page 2 of 2



Aluminum allay
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal
specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response all mating ends or 1288 bx mfr ref single material response all mating ends
Included Contact Quantity:
57 single mating end single contact grouping
Included Contact Type:
Round socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.114 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-81659/33 government specification
61343-IIIII-C-01039/33 government specification
Shelf Life:
Shelf Life:
Shelf Life: N/a
Shelf Life: N/a
Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure: Demilitarization:
Shelf Life: N/a Unit Of Measure: Demilitarization: No
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A039b0