Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-181-9009

#### **Body Style:**

Straight shape

#### **Overall Length:**

1.425 inches

## **Overall Height:**

0.481 inches

### **Overall Width:**

0.248 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.089 inches and 0.094 inches

#### Distance Between Mounting Facility Centers:

Between 1.210 inches and 1.220 inches

### Mating End Quantity:

1

# Contact Position Arrangement Style:

51 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Polarization Method:**

Mating end

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1 military specification 1st treatment response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, ty sdg military specification single material response single mating end

## **Included Contact Quantity:**

51 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact and terminal surfaces gold



**Precious Material And Weight:** 

0.051 gold grains, troy

# **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.