## NSN 5935-01-181-9368

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-181-9368

**Body Style:** 

Straight shape w/jackscrew

**Overall Width:** 

1.050 inches

**Environmental Protection:** 

Shock resistant and moisture resistant and corrosion resistant and vibration resistant and thermal shock resistant

**Distance Between Mounting Facility Centers:** 

2.478 inches

**Mating End Quantity:** 

1

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Polarization boss

Shell Type:

Solid

**Connector Locking Method:** 

Jackscrew

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Silver single mating end single contact grouping

**Insert Material:** 

Plastic epoxy single mating end

**Contact Surface Treatment Specification:** 

Qq-s-365 federal specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

**Passivate** 

**Included Contact Quantity:** 

100 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces silver

## NSN 5935-01-181-9368

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.100 silver grains, troy
Precious Material:
Silver
Shelf Life:

Unit Of Measure:

\_ ..

N/a

Demilitarization:

No

Fiig:

A039b0