## NSN 5935-01-182-2221

**Thread Class:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-182-2221

2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
3.278 inches
Overall Diameter:
1.594 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Cable Entrance Diameter:
Between 0.445 inches and 0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-19 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
330.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
18
Thread Size:
1.375 inches
Terminal Location:
Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## NSN 5935-01-182-2221

Electrical Plug Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1,
grade b federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

•

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.