

View Online at <https://aerobasegroup.com/nsn/5935-01-182-2289>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

3.278 inches

**Overall Diameter:**

1.469 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Cable Entrance Diameter:**

Between 0.445 inches and 0.750 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-4 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

41.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

30.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Cable clamp

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1, grade b federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.