# NSN 5935-01-182-4781

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-182-4781

**Body Style:** Rectangular shape **Overall Length:** 1.206 inches **Overall Height:** 0.365 inches **Body Width:** 0.240 inches **Environmental Protection:** Cold resistant and heat resistant **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 750.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** An/prc-113 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 ty ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Contact Material Specification:** 

Qq-b-750 composition a federal specification single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14 ty sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

24 single mating end single contact grouping

## **Included Contact Type:**

Flat socket single mating end single contact grouping

# NSN 5935-01-182-4781

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.