

View Online at <https://aerobasegroup.com/nsn/5935-01-182-4783>

**Body Style:**

Rectangular shape

**Overall Length:**

0.900 inches

**Overall Height:**

0.440 inches

**Body Width:**

0.238 inches

**Environmental Protection:**

Thermal shock resistant and cold resistant and heat resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**End Application:**

An/prc-113

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 ty ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:**

18 single mating end single contact grouping

**Included Contact Type:**

Flat socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.018 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.