

View Online at <https://aerobasegroup.com/nsn/5935-01-182-6628>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle, shape, internal coupling

**Environmental Protection:**

Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Sc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Compression nut

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.688 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic epoxy single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0