

View Online at <https://aerobasegroup.com/nsn/5935-01-183-9306>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

2.650 inches

**Overall Height:**

Between 0.416 inches and 0.436 inches

**Overall Width:**

0.620 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

2.406 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24w7 single mating end

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Terminal Location:**

Back single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 ty ii, grade c, cl 1 military specification single treatment response single mating end 1st contact grouping

**Terminal Type:**

Solder well single mating end 1st contact grouping

**Shell Material:**

Metal

**Shell Surface Treatment:**

Cadmium and chromate or zinc

**Shell Surface Treatment Specification:**

Qq-p-416 type 2, cl 2 federal specification 1st treatment response or astrmb633 assn standard 1st treatment response

**Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gpt-30f military specification single material response single mating end

**Included Contact Quantity:**

17 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.017 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.