

View Online at <https://aerobasegroup.com/nsn/5935-01-184-0637>

Thread Class:

2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

31.0 millimeters

Overall Diameter:

32.5 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

15-15 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Thready Qty Per Inch (tpi):

10

Thread Size:

22.0 millimeters

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Thread Tolerance Class:

6g external

Included Contact Quantity:

14 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.019 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-dod-c-38999/26 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.