

View Online at <https://aerobasegroup.com/nsn/5935-01-184-2714>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, w/o cable clamp

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Maximum Current Rating In Amps:**

1.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 single mating end single contact grouping

**Shell Type:**

Solid

**Thread Size:**

0.190 inches

**Contact Material:**

Beryllium single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact gold

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.