

View Online at <https://aerobasegroup.com/nsn/5935-01-184-5433>

Thread Class:

2a and 3b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

4.437 inches

Overall Diameter:

2.000 inches

Environmental Protection:

Shock resistant and vibration resistant and moisture resistant and corrosion resistant

Cable Entrance Diameter:

0.937 inches

Distance From Mounting Shoulder To Front Face:

1.030 inches

Mounting Facility Thickness:

0.505 inches

Threaded Device Type:

Mounting bushing and back shell

Mating End Quantity:

12

Polarization Method:

Keyway or multiple keyway and key, multiple key groove

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp and cord protector

End Application:

3810-01-144-4885

Thready Qty Per Inch (tpi):

18 and 40

Thread Size:

1.688 inches

Insert Material:

Rubber single mating end

Shell Material:

Aluminum alloy or zinc

Shell Surface Treatment:

Cadmium and chromate and zinc

Bushing Accommodation Hole Shape:

Round w/flat

Special Features:

Insert configuration 24-9

Thread Series Designator:

Unef and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0