

View Online at <https://aerobasegroup.com/nsn/5935-01-184-5433>

**Thread Class:**

2a and 3b

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling w/strain relief

**Overall Length:**

4.437 inches

**Overall Diameter:**

2.000 inches

**Environmental Protection:**

Shock resistant and vibration resistant and moisture resistant and corrosion resistant

**Cable Entrance Diameter:**

0.937 inches

**Distance From Mounting Shoulder To Front Face:**

1.030 inches

**Mounting Facility Thickness:**

0.505 inches

**Threaded Device Type:**

Mounting bushing and back shell

**Mating End Quantity:**

12

**Polarization Method:**

Keyway or multiple keyway and key, multiple key groove

**Insert Position In Deg:**

0.0 and 95.0 and 132.0 and 232.0 and 260.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Cable clamp and cord protector

**End Application:**

3810-01-144-4885

**Thready Qty Per Inch (tpi):**

18 and 40

**Thread Size:**

1.688 inches

**Insert Material:**

Rubber single mating end

**Shell Material:**

Aluminum alloy or zinc

**Shell Surface Treatment:**

Cadmium and chromate and zinc

**Bushing Accommodation Hole Shape:**

Round w/flat

**Special Features:**

Insert configuration 24-9

**Thread Series Designator:**

Unef and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0