Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-184-7911

# Body Style:

Right angle type

## **Overall Length:**

2.850 inches

# **Overall Width:**

0.400 inches

#### **Body Height:**

0.250 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and vibration resistant

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

## **Polarization Method:**

Guide pin/socket

# **Connector Locking Method:**

Friction

Terminal Location:

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Insert Material:

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end or mil-m-14, type sdg-f military specification single

material response single mating end

# Unable To Decode:

Unable to decode and unable to decode

## Included Contact Quantity:

40 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surf gold

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.