Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-184-8365

Body Style:
Straight shape threaded
Overall Length:
1.025 inches
Overall Diameter:
1.045 inches
Environmental Protection:
Hermetic
Distance From Mounting Shoulder To Front Face:
Between 0.540 inches and 0.560 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
12-dec single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Terminal Type:
Wire loop single mating end single contact grouping
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mtd
Test Data Document:
81349-mil-c-26500 specification (includes engineering type bulletins, broch

81349-mil-c-26500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms27034 government specification

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26500 spec.