Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-185-0320



## **Thread Class:**

2a and 2b

**Thread Direction:** 

Right-hand

## **Body Style:**

Hood, top opening w/clamp

## **Overall Length:**

2.594 inches

#### **Overall Height:**

2.406 inches

Overall Width:

#### 0.828 inches

Cable Entrance Diameter:

#### 0.625 inches

#### **Threaded Device Type:**

## Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

50 single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

#### Shell Type:

Hood, top opening

## **Connector Locking Method:**

Jackscrew-socket

## **Connector Cable Strain Relief Method:**

Cable clamp

## Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.138 inches

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

# NSN 5935-01-185-0320

Electrical Plug Connector - Page 2 of 2



#### Insert Material:

Plastic diallyl phthalate single mating end

## **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Aluminum

# Shell Surface Treatment:

Anodize

## **Included Contact Quantity:**

50 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.050 gold grains, troy

## **Precious Material:**

Gold

## **Thread Series Designator:**

Unc

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A039b0