NSN 5935-01-185-1468

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-185-1468 **Body Style:** Right angle type **Overall Length:** 4.594 inches **Overall Height:** 0.719 inches **Overall Width:** 0.594 inches **Unthreaded Mounting Hole Diameter:** 0.138 inches **Distance Between Mounting Facility Centers:** 4.250 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 725.0 single mating end single contact grouping **Polarization Method:** Shell Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate mineral filled single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:**

Cadmium and chromate

NSN 5935-01-185-1468

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Shell Guide Type And Location Designator:

A slot and I slot

Included Contact Quantity:

35 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.