NSN 5935-01-185-1470

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-185-1470 **Body Style:** Straight type **Overall Length:** 5.094 inches **Overall Height:** 0.422 inches **Overall Width:** 0.438 inches **Unthreaded Mounting Hole Diameter:** 0.219 inches **Distance Between Mounting Facility Centers: 4.688** inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 725.0 single mating end single contact grouping **Polarization Method:** Shell Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate mineral filled single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum

Aluminum

Shell Surface Treatment:

Chromate and cadmium

NSN 5935-01-185-1470

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Shell Guide Type And Location Designator:

A pin and I pin

Included Contact Quantity:

35 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.