# NSN 5935-01-185-1475

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-185-1475 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Pcb, external coupling **Overall Length:** 0.630 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Environmental Protection:** Corrosion resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.102 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.340 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.190 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

# NSN 5935-01-185-1475

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material:**

Plastic polytetrafluoroethylene single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Copper alloy

#### **Shell Surface Treatment:**

Gold

### **Shell Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response

### **Shell Material Specification:**

Qq-c-530 federal specification single material response

### **Insert Material Specification:**

L-p-403 federal specification single material response single mating end

### **Included Contact Quantity:**

1 single mating end single contact grouping

### **Included Contact Type:**

Coaxial socket single mating end single contact grouping

# **Precious Material And Location:**

Contact and shell surfaces gold

#### **Precious Material And Weight:**

0.105 gold grains, troy

### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unf

### Shelf Life:

N/a

## **Unit Of Measure:**

### Demilitarization:

No

# Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.