Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-185-2258

Body Style:
Single card
Overall Length:
4.196 inches
Overall Height:
1.190 inches
Overall Width:
0.531 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Distance Between Mounting Facility Centers:
3.934 inches
Board Accommodated Length:
3.615 inches single board
Board Accommodated Width:
Between 0.072 inches and 0.077 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Criticality Code Justification:
Feat
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping

AeroBase Group

Insert Material Specification: Mil-m-14f, type sdg military specification single material response single mating end **Included Contact Quantity:** 34 single mating end single contact grouping Included Contact Type: Hermaphrodite single mating end single contact grouping **Special Features:** Polarizing pin installed in contact position 21 **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.034 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14f spec.