NSN 5935-01-186-0137

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-186-0137 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/backshell **Overall Length:** 2.969 inches **Overall Diameter:** 2.170 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 280.0 Shell Type: **Connector Locking Method:** Internally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:**

1.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-186-0137

Electrical Plug Connector - Page 2 of 2



| Insert Material: |
|--|
| Rubber single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 1, grade |
| b federal specification 2nd treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416 type 2, cl 3 federal specification single treatment response |
| Included Contact Quantity: |
| 24 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.024 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.