

View Online at <https://aerobasegroup.com/nsn/5935-01-186-0148>

Body Style:

Straight shape, external coupling

Overall Length:

1.187 inches

Bushing Diameter:

0.436 inches

Overall Height:

Between 0.682 inches and 0.692 inches

Overall Width:

Between 0.682 inches and 0.692 inches

Environmental Protection:

Shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.105 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.496 inches and 0.504 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.496 inches and 0.504 inches

Distance From Mounting Shoulder To Front Face:

Between 0.605 inches and 0.645 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

An/wlr-1

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.