

View Online at <https://aerobasegroup.com/nsn/5935-01-186-0712>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.662 inches

Overall Height:

2.000 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.147 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.562 inches

Distance From Mounting Shoulder To Front Face:

Between 0.812 inches and 0.843 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-11 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Silicon single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

4 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.