

View Online at <https://aerobasegroup.com/nsn/5935-01-186-2254>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight type

**Overall Length:**

1.300 inches

**Overall Height:**

0.644 inches

**Overall Width:**

Between 0.289 inches and 0.302 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and shock proof and vibration proof

**Distance Between Mounting Facility Centers:**

1.150 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Fixed contact to contact

**Connector Locking Method:**

Friction

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Nickel single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Qq-n-290, cl 2 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, ty ii, grade d, cl 1 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

17 single mating end single contact grouping

**Included Contact Type:**

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-55302/52 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.