2b

1

Solid

32

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-186-5451



Thread Class: Thread Direction: Right-hand Body Style: Straight shape, internal coupling **Overall Length:** 1.094 inches **Threaded Device Type:** Coupling facility Mating End Quantity: **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 65.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: **Connector Locking Method:** Internally threaded shell **Radio Frequency Type Contact Characteristic Impedance In Ohms:** 75.0 single mating end single contact grouping Thready Qty Per Inch (tpi): **Thread Size:** 0.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, ty ii, cl 2, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper

Shell Surface Treatment Specification:

Mil-g-45204, ty ii, cl 1, grade c military specification 1st treatment response and mil-c-14550, cl 4 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Body and contact surface gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.