Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-186-5484

Body Style:

Right angle, card

Overall Length:

1.630 inches

Body Width:

0.325 inches

Body Height:

0.238 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

End Application:

2350-01-089-1261

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single materia

Insert Material Specification:

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

Included Contact Quantity:

32 single mating end single contact grouping

Included Contact Type:

Contact ourfaces cold

Round pin single mating end single contact grouping

Precious Material And Location:



Precious Material And Weight:

0.032 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - terminal

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/128 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.