NSN 5935-01-186-5920

Straight shape, internal coupling w/strain relief

Body Style:

Body Length:

Cadmium

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-186-5920

2.094 inches
Overall Diameter:
1.047 inches
Cable Entrance Diameter:
0.344 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Wk-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
15.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1700.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Internally threaded coupling ring
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size:
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location:
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic melamine single mating end
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type:
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp w/telescoping bushing Thread Size: 0.875 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping

NSN 5935-01-186-5920

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0