# NSN 5935-01-186-6396

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-186-6396 **Body Style:** Right angle type **Overall Length:** 6.500 inches **Overall Width:** 0.300 inches **Body Height:** 0.330 inches **Environmental Protection:** Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.068 inches **Distance Between Mounting Facility Centers:** 6.300 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction **End Application:** 5865-nc-c12-0190 **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** 

Anodize

# NSN 5935-01-186-6396

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

180 single mating end single contact grouping

#### **Included Contact Type:**

Flat pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.180 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0