## NSN 5935-01-186-8287

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-186-8287

| Body Style:   |
|---|
| Right angle type  |
| Overall Length:   |
| 6.680 inches  |
| Overall Height:   |
| 0.585 inches  |
| Overall Width:  |
| 0.575 inches  |
| Environmental Protection:   |
| Humidity resistant and thermal shock resistant  |
| Unthreaded Mounting Hole Diameter:  |
| 0.220 inches  |
| Distance Between Mounting Facility Centers:   |
| 6.350 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Polarization Method:  |
| Contact to contact polarizing keys  |
| Terminal Location:  |
| Side single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Tin single mating end single contact grouping and nickel single mating end single contact grouping  |
| Insert Material:  |
| Plastic polyester single mating end   |
| Contact Surface Treatment Specification:  |
| Mil-t-10727 military specification 1st treatment response single mating end single contact grouping |
| Terminal Type:  |
| Wire wrap single mating end single contact grouping   |
| Contact Material Specification:   |
| Qq-c-530 federal specification single material response single mating end single contact grouping   |
| Included Contact Quantity:  |
| 240 single mating end single contact grouping   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5935-01-186-8287

Electrical Receptacle Connector - Page 2 of 2



| _  |   |   |   |   |   |     |    |   |   |  |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | • | iza | 31 | ^ | n |  |
|    |   |   |   |   |   |     |    |   |   |  |

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-t-10727 spec.