## NSN 5935-01-187-6157

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-187-6157

**Body Style:** Right angle type **Overall Length:** 3.595 inches **Overall Height:** 0.740 inches **Environmental Protection:** Vibration resistant and thermal shock resistant and shock resistant and moisture resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** Between 0.122 inches and 0.127 inches **Distance Between Mounting Facility Centers:** 3.275 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **End Application:** 4935-01-114-3919 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, grade c, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** 

moort material opcomouncin.

Mil-p-46161 military specification single material response single mating end

**Included Contact Quantity:** 

46 single mating end single contact grouping

## NSN 5935-01-187-6157

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.046 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.