

View Online at <https://aerobasegroup.com/nsn/5935-01-187-6174>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.290 inches

Overall Height:

Between 1.812 inches and 1.832 inches

Overall Width:

Between 1.812 inches and 1.832 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.157 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Distance From Mounting Shoulder To Front Face:

Between 0.785 inches and 0.790 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

25-46 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

95.0 and 132.0 and 232.0 and 260.0 and 345.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.219 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Features Provided:

Scoopproof design

Thready Qty Per Inch (tpi):

18

Thread Size:

1.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

4 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.070 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27656 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.