Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-187-6201

View Online at https://aerobasegroup.com/nsn/5935-01-187-6201
Thread Class:
2b and 2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
1.435 inches
Overall Height:
0.850 inches
Overall Width:
0.472 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and moisture resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
1.225 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
51 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Post jacksocket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping



Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 ty ii, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 ty ii, cl 3 federal specification all treatment responses
Insert Material Specification:
Mil-m-14 ty sdgf military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
51 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.051 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.
Mil-std (military Standard):