## NSN 5935-01-187-6209

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-187-6209

**Body Style:** 

Straight shape w/solder mount

**Overall Length:** 

1.096 inches

**Overall Diameter:** 

0.750 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Sep-98 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

95.0 and 132.0 and 232.0 and 260.0 and 345.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 200.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

Tin

**Shell Surface Treatment Specification:** 

Mil-t-10727, type 1 military specification single treatment response

**Included Contact Quantity:** 

3 single mating end single contact grouping

## NSN 5935-01-187-6209

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mount
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27471 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-q-45204 spec.