

View Online at <https://aerobasegroup.com/nsn/5935-01-187-7480>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.343 inches

**Overall Diameter:**

0.650 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Tnc all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

11000.0 megahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.438 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2, grade c military specification single treatment response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial pin all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-55339/36 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.