

View Online at <https://aerobasegroup.com/nsn/5935-01-188-6323>

Body Style:

Straight shape, flush mount

Overall Length:

1.061 inches

Overall Height:

3.075 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.112 inches and 0.118 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.060 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

30 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Solder well all mating ends all contact groupings

Contact Material Specification:

Qq-c-533 federal specification single material response all mating ends all contact groupings

Guide Design And Location:

Hexagon shape female post left-hand at 6 oclock and hexagon shape female post center at 6 oclock and hexagon shape female post right-hand at 6 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification all treatment responses

Shell Material Specification:

Qq-a-591, a380 federal specification single material response

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.052 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.