# NSN 5935-01-188-8465

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-188-8465

Body	Style:
------	--------

Straight shape, internal coupling w/backshell

**Overall Length:** 

1.300 inches

**Overall Diameter:** 

1.890 inches

# **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Mating End Quantity:** 

1

# **Contact Position Arrangement Style:**

61 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

# **Insert Position In Deg:**

25.0

# Shell Type:

Solid

# **Connector Locking Method:**

Spring friction

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Insert Material:**

Rubber single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium and chromate and nickel and zinc

# **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 federal specification 1st treatment response and qq-p-416, type 2, cl 1 federal specification 2nd treatment response

# **Included Contact Quantity:**

61 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# NSN 5935-01-188-8465

Electrical Plug Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.