

View Online at <https://aerobasegroup.com/nsn/5935-01-188-8483>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, flush mount

Overall Length:

1.215 inches

Overall Height:

Between 2.032 inches and 2.062 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.720 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.318 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

67 single mating end

Contact Removability:

Removable single mating end all contact groupings

Shell Type:

Solid

End Application:

4920-01-146-5599

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

64 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.079 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-81659/65 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.