## NSN 5935-01-188-8483



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-188-8483 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.215 inches **Overall Height:** Between 2.032 inches and 2.062 inches **Overall Width:** Between 1.985 inches and 2.015 inches **Environmental Protection:** Vibration resistant and shock resistant and salt water resistant and humidity resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.720 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.437 inches **Distance From Mounting Shoulder To Front Face:** 0.318 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 67 single mating end **Contact Removability:** Removable single mating end all contact groupings Shell Type: Solid **End Application:** 4920-01-146-5599 Thready Qty Per Inch (tpi): 40 **Thread Size:** 

0.112 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end all contact groupings

## NSN 5935-01-188-8483

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
64 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.079 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-81659/65 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.