## NSN 5935-01-188-8484

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-188-8484

**Body Style:** Right angle type **Overall Length:** 6.180 inches **Overall Height:** 0.645 inches **Overall Width:** 0.595 inches **Environmental Protection:** Vibration resistant and thermal shock resistant and shock resistant and moisture resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** Between 0.096 inches and 0.101 inches **Distance Between Mounting Facility Centers:** 5.850 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1300.0 single mating end single contact grouping **End Application:** 1260-01-I11-0148 **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 ty ii, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-46161 military specification single material response single mating end

**Included Contact Quantity:** 

165 single mating end single contact grouping

## NSN 5935-01-188-8484

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.165 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.