NSN 5935-01-189-1888

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-189-1888

Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.291 inches Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.291 inches Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Body Style: Straight shape, internal coupling Overall Length: 1.291 inches Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Straight shape, internal coupling Overall Length: 1.291 inches Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Overall Length: 1.291 inches Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
1.291 inches Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Overall Diameter: 0.625 inches Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Environmental Protection: Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type:
Threaded Device Type: Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Coupling facility Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Mating End Quantity: 2 Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Contact Position Arrangement Style: Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Tnc all mating ends Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Contact Removability: Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Removable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Shell Type: Solid
500.0 all mating ends single contact grouping Shell Type: Solid
Shell Type: Solid
Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends single contact grouping
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 type 1, cl 2, grade c military specification single treatment response all mating ends single contact grouping
Shell Material:
Copper alloy
Included Contact Quantity:

1 all mating ends single contact grouping

NSN 5935-01-189-1888

Connector Adapter - Page 2 of 2



Included Contact Type:
Coaxial socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-a-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-a-55339/33 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-std (military s