Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-189-1893

#### **Body Style:**

Straight shape, external coupling

#### **Overall Length:**

0.890 inches

## **Overall Height:**

1.250 inches

#### **Overall Width:**

1.250 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

#### 0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 0.969 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

## 0.969 inches

Distance From Mounting Shoulder To Front Face:

#### 0.710 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

24 number 20 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

24.0 and 135.0 and 199.0 and 240.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Metal ferrous single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Insert Material:

Glass single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping



#### **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Steel

Shell Surface Treatment:

Tin

Included Contact Quantity:

24 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.024 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-c-83723/79 government specification

### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.