

View Online at <https://aerobasegroup.com/nsn/5935-01-189-2484>

Thread Class:

2b

Thread Direction:

Right-hand

Overall Length:

0.705 inches

Overall Height:

0.625 inches

Overall Width:

0.260 inches

Environmental Protection:

Cold resistant and heat resistant and corrosion resistant and vibration resistant and shock resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

0.102 inches

Distance Between Mounting Facility Centers:

0.481 inches

Distance From Mounting Shoulder To Front Face:

0.442 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

2.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.150 inches

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204b type 1, grade a or c, cl 2 military specification 1st treatment response single mating end single contact grouping and

mil-c-14550 cl 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.001 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204b spec.