NSN 5935-01-189-6780

Electrical Receptacle Connector - Page 1 of 2



Ziosinoan ricooptacio Commocion in ago in circ
View Online at https://aerobasegroup.com/nsn/5935-01-189-6780
Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Right angle type
Overall Length:
1.250 inches
Body Height:
0.440 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.937 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
End Application:
Keyer group kg-81
Thready Qty Per Inch (tpi):
32 and 40
Thread Size:
0.138 inches and 0.112 inches
Terminal Location:

Side single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping

NSN 5935-01-189-6780

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-male and location-left handandjackscrew type-female and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.