

View Online at <https://aerobasegroup.com/nsn/5935-01-189-7539>

Thread Class:

2a and 3b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.662 inches

Overall Height:

1.375 inches

Overall Width:

1.375 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

Distance From Mounting Shoulder To Front Face:

0.750 inches

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

12

Contact Position Arrangement Style:

18-1 single mating end

Polarization Method:

Keyway or multiple keyway and key, multiple key groove

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches and 0.290 inches

Thready Qty Per Inch (tpi):

18 and 40

Thread Size:

1.125 inches and 1.250 inches and 1.375 inches

Insert Material:

Rubber single mating end

Shell Material:

Aluminum alloy or zinc

Shell Surface Treatment:

Cadmium and chromate and zinc

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unc

Specification Data:

96906-ms3402 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.