NSN 5935-01-190-5288

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-190-5288

Body Style:

Straight edge type w/card guide

Overall Length:

4.350 inches

Overall Width:

0.300 inches

Body Height:

Between 0.580 inches and 0.630 inches

Environmental Protection:

Heat resistant and humidity resistant and salt water resistant and thermal shock resistant and vibration proof

Board Accommodated Length:

4.200 inches single board

Board Accommodated Width:

Between 0.075 inches and 0.083 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

End Application:

Mk72m15 sdc

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, grade c or d military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-c-533, alloy 172 federal specification single material response single mating end single contact grouping

NSN 5935-01-190-5288

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 44 single mating end single contact grouping Included Contact Type: Bifurcated spring single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.044 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Mil-std (military Standard):

Mil-g-45204 spec.

Fiig: A039b0