## NSN 5935-01-191-8264

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-191-8264

**Body Style:** Straight edge type **Overall Length:** 3.426 inches **Overall Height:** 0.665 inches **Overall Width:** 0.335 inches **Distance Between Mounting Facility Centers:** 3.240 inches **Board Accommodated Length:** 3.000 inches single board **Board Accommodated Width:** Between 0.085 inches and 0.091 inches **Mating End Quantity: Contact Position Arrangement Style:** 92 single mating end **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1200.0 single mating end single contact grouping **End Application:** F-16 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Beryllium single mating end single contact grouping and copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp and solder single mating end single contact grouping **Contact Material Specification:** Qq-b-626 federal specification single material response single mating end single contact grouping **Included Contact Quantity:** 92 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping

Contact surf gold

**Precious Material And Location:** 

## NSN 5935-01-191-8264

Electrical Receptacle Connector - Page 2 of 2



| Precious Material:           |
|------------------------------|
| Gold                         |
| Shelf Life:                  |
| N/a                          |
| Unit Of Measure:             |
|                              |
| Demilitarization:            |
| No                           |
| Fiig:                        |
| A039b0                       |
| Mil-std (military Standard): |

Mil-g-45204 spec.